

Interior
Latex

FLAT

Low
Odor



ZERO TOXINS. INFINITE BEAUTY.®

Mythic Pro™ is a non-toxic, ultra low odor high quality paint that provides durability and coverage without cancer-causing toxins or VOC's that can off-gas for years. Stronger, safer, smarter paint.® Now that's a breath of fresh air.

PERFORMANCE GUARANTEE

This product is the result of extensive research and testing. If this product fails to perform when used according to label instructions, return the unused portion with your receipt to the place of purchase. We will furnish an equivalent amount of paint at no cost or will refund the purchase price. This guarantee does not include labor or the cost of labor for the application of any paint. This guarantee gives you specific legal rights, and you may have other rights which vary from state to state.

Zero VOC
Volatile Organic Compounds



SAFE FOR
PEOPLE



SAFE FOR
PETS



SAFE FOR
the EARTH

This paint meets criteria for coatings
used in LEED® certified buildings.

4200 Mamie Street, Suite 120 • Hattiesburg, MS 39402 • Customer Support: 1.888.714.9422 • Fax: 1.888.714.9423

www.mythicpaint.com



Interior
Latex

FLAT

Low
Odor

RECOMMENDED USE

Mythic® Pro Interior Latex Flat is a high hiding paint designed for the professional contractor for use over properly prepared interior walls of plaster, wallboard, masonry, and tightly adhered wallpaper. It is ideal for residences, office buildings, hotel rooms, stores, restaurants, nursing homes, schools, hospitals, and other areas where a spatter resistant non-reflective finish with superior touch up is desired.

This product can be used in occupied areas without typical odor complaints because of the very low odor during application and drying.

SURFACE PREPARATION

See Surface Preparation Section on Paint Label.

Color - For drastic color changes, Mythic® Multi-Purpose Primer may be used as a base coat. For deep and accent colors, Mythic® Tintable Accent Primer may be used for optimal coverage and color development.

Drywall - Mythic® Pro Interior Latex Drywall Primer should be used to seal any unprimed drywall or patching.

Plaster/Masonry - Allow new stucco, plaster, and masonry to cure 30 days before priming. Use Mythic® Multi-Purpose Primer to seal surfaces before painting.

Wood/Paneling/Wallcovering - Seal the surface with Mythic® Multi-Purpose primer. Mythic Pro™ Drywall Primer may be used on non-bleeding wood surfaces.

Metal - Prime with an appropriate primer before applying this product.

EQUIPMENT

Conv. Spray:	40 PSI TIP: 704/FX
Airless Spray:	1800 - 2400 PSI TIP: .015" - .021"
Brush:	Polyester or Nylon
Roller:	3/8" - 1/2" Nap Cover
Pad:	Standard

THINNER & CLEAN-UP

Thinning is not recommended, but if necessary, use clean water sparingly. Soap and water clean-up.

LIMITATIONS

- Do not apply when air, surface, or product temperature is below 50°F (10°C) or if temperature might drop to this level within 4 hours of application.
- Do not apply in temperatures above 90°F (32°C).

PACKAGING

- Gallons and 5 Gallons

COLORS

- 990 palette colors
- Computer color matching available

SPECIFICATION DATA **

Type:	Acrylic Latex
Finish:	Flat
» Sheen:	5 Max @ 85°
% Solids (varies with color):	
» By Weight:	48 ± 2%
» By Volume:	29 ± 2%
Wt./Gallon: (White only):	11.40 lbs.
Flashpoint:	212°F (PMCC)
VOC lbs./gal (max):	0
VOC grm/ltr (max):	0
Thinner:	Water
Clean-up:	Soap and Water
Dry Time:	
» To Touch:	2 hours
» To Recoat:	4-8 hours
» To Service:	Overnight

Note: Adding large amounts of zero VOC colorant can dramatically slow dry/cure time.

Thickness:	
» Dry:	1.5 mil
» Wet:	4.0 mil
Coverage:	400 sq. ft./gal (on smooth surfaces)
Flame Spread Rate:	Class A (0-25 on non-combustible surfaces)

**Product Data is based on MP300-A