

Interior
Latex

DRYWALL
PRIMER

Low
Odor



ZERO TOXINS. INFINITE BEAUTY.®

Mythic Pro™ is a non-toxic, ultra low odor high quality paint that provides durability and coverage without cancer-causing toxins or VOC's that can off-gas for years. Stronger, safer, smarter paint.® Now that's a breath of fresh air.

PERFORMANCE GUARANTEE

This product is the result of extensive research and testing. If this product fails to perform when used according to label instructions, return the unused portion with your receipt to the place of purchase. We will furnish an equivalent amount of paint at no cost or will refund the purchase price. This guarantee does not include labor or the cost of labor for the application of any paint. This guarantee gives you specific legal rights, and you may have other rights which vary from state to state.

Zero VOC
Volatile Organic Compounds



SAFE FOR
PEOPLE



SAFE FOR
PETS



SAFE FOR
the EARTH

This paint meets criteria for coatings
used in LEED® certified buildings.

4200 Mamie Street, Suite 120 · Hattiesburg, MS 39402 · Customer Support: 1.888.714.9422 · Fax: 1.888.714.9423

www.mythicpaint.com

LEGENDARY PERFORMANCE

Mythic

NON-TOXIC
PAINT

Pro

Interior
Latex

DRYWALL
PRIMER

Low
Odor

RECOMMENDED USE

Mythic® Pro Interior Latex Drywall Primer is designed for the professional contractor to seal new drywall, aged plaster, and masonry. It can be used to prepare previously painted surfaces and tightly adhered wallpaper for final topcoat application. Glossy surfaces should be dulled before priming.

This product can be used in occupied areas without typical odor complaints because of the very low odor during application and drying.

SURFACE PREPARATION

See Surface Preparation Section on Paint Label.

New Surfaces:

Non-Bleeding Wood, Plaster:

Mythic® Pro Interior Latex Primer

Drywall:

Mythic® Pro Interior Latex Primer

Metal:

Not recommended

EQUIPMENT

Conv. Spray:	40 PSI TIP:704/FX
Airless Spray:	1800 - 2400 PSI TIP:.015" - .021"
Brush:	Polyester or Nylon
Roller:	3/8" - 1/2" Nap Cover
Pad:	Standard

THINNER & CLEAN-UP

Thinning is not recommended, but if necessary, use clean water sparingly. Soap and water clean-up.

LIMITATIONS

- Do not apply when air, surface, or product temperature is below 50°F (10°C) or if temperature might drop to this level within 4 hours of application.
- Do not apply in temperatures above 90°F (32°C).

PACKAGING

Gallons and 5 Gallons

COLORS

Tintable White

Note: Can be tinted with up to 2 oz. of colorant per gallon.

SPECIFICATION DATA

Type:	Acrylic Latex
Finish:	Flat
» Sheen:	5 Max @ 85°
% Solids (varies with color):	
» By Weight:	42 ±2%
» By Volume:	24 ±2%
Wt./Gallon: (White only):	10.93 lbs.
Flashpoint:	212°F (PMCC)
VOC lbs./gal (max):	0
VOC grm/ltr (max):	0
Thinner:	Water
Clean-up:	Soap and Water
Dry Time:	
» To Touch:	2 hours
» To Recoat:	4-8 hours
» To Service:	Overnight
Thickness:	
» Dry:	1.0 mil
» Wet:	4.0 mil
Coverage:	350-400 sq.ft./gal (on smooth surfaces)
Flame Spread Rate:	Class A (0-25 on non-combustible surfaces)